

TEST REPORT

NO.: A001T101225015001

Date: Dec 27, 2010

Page 1 of 3

Customer: Cheung Kee Canvas Ltd.

Address: G/F.,352,Reclamation St.,Kln.,H.K.

Report on the submitted sample said to be

Sample name: Flame Retardant Scaffolding Net

Model: 2Mx9M, 2Mx18M

Item/Lot No. : /

Material: /

Buyer: /

Supplier: /

Manufacturer: /

Country of Origin: /

Country of Destination: /

Labelled Age Grading: /

Sample received date: Dec 25, 2010

Testing period: From Dec 25, 2010 to Dec 27, 2010

Testing Requested

For compliance with the European Standard on Safety of Toys:

-EN 71-2:2006+A1:2007- Flammability

Conclusion

-EN 71-2: The submitted sample complied with the requirement.

*****FOR FURTHER DETAILS, PLEASE REFER TO THE FOLLOWING PAGE(S)*****

Written by: Stacey

Tested by: Andy

Inspected by: James

Approved by: Jeemah

TEST REPORT

NO.: A001T101225015001

Date: Dec 27, 2010

Page 2 of 3

Results:

Part 2: Flammability

Section	Description	Result
4	REQUIREMENTS	
4.1	General	Pass

Note:

4.1 The following materials shall not be used in the manufacture of toys:

Celluloid (cellulose nitrate), except when used in varnish, paint or glue, or in balls of the type used for table tennis or similar games, and materials with the same behaviour in fire as celluloid. Specific materials to which the test flame is applied in order to check compliance of the toy with requirements in 4.2 to 4.5 are considered to comply with this requirement if the toy meets its appropriate requirements in 4.2 to 4.5;

Materials with a piled surface which produce surface flash on the approach of a flame. Piled surfaces showing no momentary area of flame over the area of the piled surface remote from the test flame are considered to meet this requirement;

Highly flammable solids.

In addition, toys shall not contain flammable gases, highly flammable liquids, flammable liquids, flammable gels except as provided for below:

Flammable liquids, flammable gels and preparations supplied in sealed containers having a maximum volume of 15 ml per container;

Highly flammable liquids and flammable liquids being entirely retained within a porous material in capillary channels of writing instruments;

Flammable liquids with a viscosity greater than $260 \times 10^{-6} \text{m}^2/\text{s}$ corresponding to a flow time of more than 38 s when determined in accordance with EN ISO 2431 using cup No. 6;

Highly flammable liquids contained in toys covered in EN 71-5.

NOTE: Different legal requirements may exist in non-EU countries.

Note:

- Photo is included.

TEST REPORT

NO.: A001T101225015001

Date: Dec 27, 2010

Page 3 of 3

Photograph of sample



Flame Retardant Scaffolding Net

End of Report