

Model No. CK15oz	High Tenacity Polyester PVC Laminated Fabrics
General Applications:	Construction, Marine (Field) covers, Storage covers and many other applications
Colors:	Silver/Black, Silver/White, Silver/Yellow, Silver/Blue, Silver/Orange, Silver/Green
Available Grades:	Fire-Retardant, Ultra-Violet, Anti-Mildew, Anti-Cold
Type of Products:	Roll Type
Flammability Test Method:	Test method 2 of NFPA 701 2004



抗水
Water
Resistant



不變形
Dimensional
Stability



阻燃
Flame
Retardant



長壽命
Long
Lasting



抗紫外線
UV
Resistant



色牢度
Color
Fastness

Physical Properties:

Fabric Detail 網布規格	1000D x 1000D x 20 x22			
Item 項目名稱	Test Method 執行標準	Unit 單位	Value 數據	
Thickness 厚度	DIN53353	mm	0.55	
Total Weight 總重量	DIN53352	g/m ²	580.3	
Tensile Strength 拉伸強度	DIN53354	N/5cm	經 Warp	2526.6
			緯 Weft	2377.9
Elongation at Break 斷裂伸長率	DIN53354	%	經 Warp	19.7
			緯 Weft	21.7
Tear Strength 撕裂強度	DIN53363	N	經 Warp	410
			緯 Weft	361
Adhesion of Coating Strength 剝離負荷	DIN53357	N/5cm	經 Warp	116.5
			緯 Weft	110.8
Remarks 備註				

This technical data is offered as helpful suggestion only.
It's accurate to the best of our knowledge at time of
printing.