

Model No.	CK18oz PVC TARPAULIN
General Applications:	Welding Protection · Gas Station · Oil Station Works Protection, Construction and many other applications
Colors:	White, Green, Silver
Available Grades:	Fire-Retardant, Ultra-Violet, Anti-Mildew, Anti-Cold
Type of Products:	Roll Type
Size:	0.5mm x 72"
Flammability Test Method:	NFPA 415-2013 Clause 6.2.1



抗水
Water
Resistant



不變形
Dimensional
Stability



阻燃
Flame
Retardant



長壽命
Long
Lasting



抗紫外線
UV
Resistant



色牢度
Color
Fastness

Physical Properties:

Fabric Detail 網布規格	1000D x 1000D x 20 x22			
Item 項目名稱	Test Method 執行標準	Unit 單位	Value 數據	
Thickness 厚度	DIN53353	mm	0.55	
Total Weight 總重量	DIN53352	g/m2	783.9	
Tensile Strength 拉伸強度	DIN53354	N/5cm	經 Warp	2621.6
			緯 Weft	2461.5
Elongation at Break 斷裂伸長率	DIN53354	%	經 Warp	15.4
			緯 Weft	21.6
Tear Strength 撕裂強度	DIN53363	N	經 Warp	388
			緯 Weft	363
Adhesion of Coating Strength 剝離負荷	DIN53357	N/5cm	經 Warp	126
			緯 Weft	115
Remarks 備註				

This technical data is offered as helpful suggestion only.
It's accurate to the best of our knowledge at time of
printing.